



Minipack 1.6kW System with bulk feed DC output



Minipack 1.6kW System with DC distribution and Controller

Minipack System

Power Supply Systems 48V, 1.6kW

Compact and cost effective power supply system

The Minipack system has been specifically designed to meet any requirement in terms of power, functionality and cost. Realization of Minipack systems is possible by fitting up to 2 rectifiers across 1U 19" shelf including controller and DC distribution.

Applications

Wireless, fiber and fixed line communication

Today's communications demand state of the art, cost efficient and compact DC power systems. The 1U Minipack system delivers a cost- efficient power solution that can be easily adapted for applications where there is limited cabinet space.

Broadband and network access

Increasing network speed demands flexible and expandable DC power solutions. Minipack is your key building block for future needs.

Product Description

The Minipack 1U is a compact power system, which can take up to two Minipack modules, Compact controller, load distribution and battery distribution. The system is available in 2 variants:

1. As a bulk feed solution with just terminal blocks for bulk feed to remote distribution
2. As a fully integrated power solution that can accommodate the rectifiers, controller, load and battery distribution

Both variants are only 1U in height, and incorporate a unique slide out mechanism. This allows for easy-access to the AC, DC and signal connection point, even with other equipment mounted directly above or below. The shallow depth of only 250 mm makes this an ideal solution for ETSI cabinets or other depth-restricted application

Key Features

Compact design

The small system dimensions are ideal for ETSI or small cabinet solutions.

Bulk-feed or integrated distribution

Select either a bulk-feed or integrated distribution to meet your power solution requirements.

Digital controllers

The controller is digitalized, enabling excellent monitoring and regulation characteristics.

Heat management

Front-to-back air flow with chassis-integrated heat sinks gives the module the most suitable working environment and no limitations in the scalability of the desired system solution.

Unique connection

A true plug-and-play connection system: time-to-install and cost-reducing solution.

Global approvals

Minipack is CE marked, UL recognized for worldwide installation.

Minipack PS Systems – 48V, 1.6kW

Additional Technical Specifications

| AC Input | |
|------------------|--|
| Voltage | 1 or 2 x single phase feeds (85VAC – 300VAC) Field configurable |
| AC Connector | Screw terminals, 2.5 mm2 [12 AWG] |
| Maximum Current | See Minipack datasheet |
| Input Protection | <ul style="list-style-type: none"> Internal fuses in rectifier module |

| Monitoring | |
|----------------------|---|
| Monitoring Unit | See Compack datasheet |
| Local Operation | WEB interface via standard browser using WebPower |
| Remote Operation | WebPower (WEB Interface, SNMP protocol and email) |
| Alarm Relays | 3 x Potential free change over contacts (NO, NC, C) |
| Visual Indications | <ul style="list-style-type: none"> Green LED – System ON Yellow LED – Minor alarm(s) Red LED – Major alarm(s) |
| Digital Inputs | <ul style="list-style-type: none"> 3 x multipurpose inputs. Can be configured for temperature measurement, digital or analogue monitoring |
| Current Measurements | <ul style="list-style-type: none"> Battery current Rectifier current |
| Alarms | <ul style="list-style-type: none"> Load fuse alarm Battery fuse alarm LVD operated Low output voltage alarms (2 individual alarm levels) High output voltage alarms (2 individual alarm levels) Battery capacity Temperature alarm Symmetry alarm and more |

| DC Output | |
|-----------|-----------------------------|
| Voltage | 48VDC |
| Power | 400-1600W (max 33A @ 48VDC) |

| DC Distribution Options | |
|-------------------------|--|
| Load fuses | <ul style="list-style-type: none"> Bulk feed output only Up to 6pcs 5x20mm fuses (2-16A) |
| Battery breakers | <ul style="list-style-type: none"> Up to 2 MCB plug-in type (30A) |
| Programmable LVD | <ul style="list-style-type: none"> LVBD: 30A |

| Connections | |
|--|--|
| Battery breaker/ bulk feed connections | Terminal blocks (up to 10mm2) |
| Load fuse connections | Pluggable terminal blocks on the front, up to 4.0 mm2 [AWG 11] |
| Alarm connections | Pluggable terminal blocks, up to 1.5 mm2 [AWG 12] |
| System | Extractable from frame for easy access |

| Other Specifications | |
|---------------------------|--|
| Isolation | <ul style="list-style-type: none"> 3.0 KVAC – input and output 1.5 KVAC – input earth 0.5 KVDC – output earth |
| Operating temp. | -40 to +75°C (-40 to +167°F) |
| Storage temp. | -40 to +80°C (-40 to +176°F) |
| Dimensions | 19" mounting (446mm + brackets) 1U height and 250mm depth Recommended cabinet depth is min 300mm |
| Weight (excl. rectifiers) | Approx. 2.66kg [5.64lbs] |

| Applicable Standards | |
|----------------------|---|
| Electrical safety | IEC 60950-1 UL 60950-1 |
| EMC | <ul style="list-style-type: none"> ETSI EN 300 386 V.1.3.2 (telecommunication network) EN 61000-6-1 (immunity, light industry) EN 61000-6-2 (immunity, industry) EN 61000-6-3 (emission, light industry) EN 61000-6-4 (emission, industry) |
| Environment | ETSI EN 300 019 ETSI EN 300 132-2 |

Ordering Information

| Part no. | Description |
|--------------|---|
| CTOM0201.xxx | Minipack 1U – Sales configured system (CTO) |
| 241117.130 | Minipack Rectifier, 48VDC 800W |
| 241117.120 | Minipack Rectifier, 48VDC 400W |
| 242100.400 | Compack controller |

Specifications are subject to change without notice

CTOM0201.DS3 – v1

www.eltekevalere.com

Headquarter:
Eltek Valere
 Gråterudv. 8, PB 2340 Strømsø, 3003 Drammen,
 Norway
 Phone: +47 32 20 32 00 Fax: +47 32 20 32 10

